









DESCO WORKSURFACE MAT SELECTION CHART


RUBBER*

Product Name	Images	Thickness	Material Construction	Resistance (Rtt in ohms) Per ANSI/ESD S4.1	Surface	Best Application	Special Features	Hardness Shore A Per ASTM D2240	Compatible w/ Monitors
Statfree T2 Plus™ Dissipative Dual Layer Rubber		0.060"	Two-Layer	Color Side: $1 \times 10^6 < 1 \times 10^9$ Black Side: $< 1 \times 10^5$	Light Texture	Area w/ chemicals & solder used	UV inhibitors added to mat	65 ± 5	Yes
Statfree UC2™		0.080"	Two-Layer	Color Side: $1 \times 10^6 < 1 \times 10^9$ Black Side: $< 1 \times 10^5$	Light Texture	Clean room; Class 100-1000	Clean packaged version available	70 ± 5	Yes
Statfree J™		0.125"	Single-Layer	Color Side: $1 \times 10^6 < 1 \times 10^9$	Open Cell Sponge	Cushion for product storage	Pre taped tray liners	45 ± 5	No
Dual-Layer Rubber		0.060"	Two-Layer	Color Side: $1 \times 10^6 < 1 \times 10^9$ Black Side: $< 1 \times 10^5$	Smooth	Area w/ chemicals & solder used	Economical	60 ± 5	Yes

VINYL

Statfree Z2™		0.125"	Three-Layer	Color Side: $1 \times 10^6 < 1 \times 10^9$	Light Emboss	Light duty Manufacturing	Cushion bottom layer	45 ± 5	Yes
Statfree O™		0.375"	Three-Layer	Color Side: $1 \times 10^6 < 1 \times 10^9$	Light Emboss	Impact energy diffusion	Double cushion layer	45 ± 5	Yes
Statfree B2™		0.060"	Two-Layer	Color Side: $1 \times 10^6 < 1 \times 10^9$ Black Side: $< 1 \times 10^5$	Light Emboss	Lite duty manufacturing	Low-charge flame retardant additive	80 ± 5	Yes
Trustat® B80		0.080"	Single-Layer	Color Side: $1 \times 10^6 < 1 \times 10^9$	Light Texture	Shelf liners	Economical	85 ± 5	Not Recommended

DISPOSABLE

Disposable ESD Mats		0.060"	Fiberboard w/ Internal Conductive Layer	Color Side: $1 \times 10^6 < 1 \times 10^9$	N/A	Harsh chemical environments	Volume Dissipative	N/A	Yes
-------------------------------------	---	--------	---	--	-----	-----------------------------	--------------------	-----	-----

RoHS, REACH, and Conflict Minerals Statement:
See [RoHS, REACH, and Conflict Minerals Statement](#) at Desco.com
Limited Warranty
See Desco's [Limited Warranty](#) at Desco.com

*Rubber has higher Heat Resistance than Vinyl and is preferred for soldering applications.

© 2020 DESCO INDUSTRIES INC
Employee Owned



Desco
Phone: West (909) 627-8178 | East (781) 821-8370
e-mail: Service@Desco.com
Web: Desco.com

